

MODEL 440 WAINSCOT WALL PANELS

GUIDE SPECIFICATION

Model 440- _____ Wall Wainscot shall be _____ wide x _____ high as manufactured by Institutional Products, Inc., Indianapolis. Indiana.

Panel shall be constructed with _____ lb. density foam _____ thick cemented to 3/8" waferboard and covered with polyester reinforced vinyl fabric. The fabric shall be folded and stapled securely to the back side of the backer board. Top and bottom of panels shall have a 1" nailing margin to secure the panels.

Vinyl Fabric covering, 14 ounce per square yard, shall be fire-rated as self-extinguished and registered as approved by the California State Fire Marshal. Test methods utilized are comparable to standards of UL-214 and NFPA-701. The material contains anti-bacterial and fungi-resistant treatment to prevent mildew and rot.

Colors available: Red, White, Dark Blue, Light Blue, Maroon, Gray, Yellow, Dark Green, Beige and Black.

Model #	Foam Thickness	Density
440-351	1½" Thick Urethane Foam	3.5 lb. Density
440-352	2" Thick Urethane Foam	3.5 lb. Density
440-601	1½" Bonded Foam	6 lb. Density
440-602	2" Bonded Foam	6 lb. Density

Fire Resistant Wall Padding

Panel shall be constructed with state-of-the-art, low smoke, fire resistant polychloroprene open-cell foam cemented to 3/8" waferboard and covered with polyester reinforced vinyl fabric. The fabric shall be folded and stapled securely to the back side of the backer board. Top and bottom of panels shall have a 1" nailing margin to secure the panels.

Vinyl Fabric covering, 14 ounce per square yard, shall be fire-rated as self-extinguished and registered as approved by the California State Fire Marshal. Test methods utilized are comparable to standards of UL-214 and NFPA-701. The material contains anti-bacterial and fungi-resistant treatment to prevent mildew and rot.

Colors available: Red, White, Dark Blue, Light Blue, Maroon, Gray, Yellow, Dark Green, Beige and Black.

Model #	Foam Thickness	Density
440-451	1½" Thick Polychloroprene Foam	4.5 lb. Density
440-452	2" Thick Polychloroprene Foam	4.5 lb. Density